

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 01, 2019

Revision: February 01, 2019

## 1 Identification


- **Product identifier**
- **Trade name:** Stinger® 32-Caliber Rubber Balls  
Stinger® 32-Caliber Rubber Balls w/Safety Clip
- **Product code:**  
1090 (1011582)  
1090SC (1152928) - w/ Safety Clip
- **Recommended use and restriction on use**
- **Recommended use:** Explosive product.
- **Restrictions on use:** Contact manufacturer/supplier
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Safariland, LLC  
13386 International Parkway  
Jacksonville, FL 32218  
Customer Care (800) 347-1200
- **Information department:** Customer Care Department
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)



## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Expl. 1.4 H204 Fire or projection hazard.

---

- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**  
  
GHS01
- **Signal word:** Warning
- **Hazard statements:**  
H204 Fire or projection hazard.
- **Precautionary statements:**  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P250 Do not subject to grinding/shock/friction.  
P372 Explosion risk in case of fire.  
P373 DO NOT fight fire when fire reaches explosives.  
P374 Fight fire with normal precautions from a reasonable distance.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **HMIS-ratings (scale 0 - 4)** Warning: Contains lead salt(s). Long-term health hazard.

---

- **Other hazards**

(Cont'd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 01, 2019

Revision: February 01, 2019

**Trade name: Stinger® 32-Caliber Rubber Balls**  
**Stinger® 32-Caliber Rubber Balls w/Safety Clip**

(Cont'd. of page 1)

## Explosive Product Notice











PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that they are dealing with a powerful force and that various devices and methods have been developed to assist them in directing this force. They should realize that this force, if misdirected, may either kill or injure both themselves and their fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, they should consult the manufacturer before use.

## 3 Composition/information on ingredients


### Chemical characterization: Mixtures

#### Components:

7778-74-7	Potassium perchlorate  Ox. Sol. 1, H271  Acute Tox. 4, H302	20-40%
7429-90-5	Aluminium  Pyr. Sol. 1, H250; Water-react. 2, H261	20-40%
7439-95-4	magnesium powder (pyrophoric)  Pyr. Sol. 1, H250; Water-react. 1, H260	20-40%
7757-79-1	Potassium nitrate  Ox. Sol. 2, H272	5-10%
7440-50-8	Copper	1-5%
9004-34-6	cellulose	1-5%
7704-34-9	Sulfur  Skin Irrit. 2, H315	1-5%
592-87-0	lead dithiocyanate  Carc. 2, H351; Repr. 1A, H360; STOT RE 2, H373  Acute Tox. 4, H302; Acute Tox. 4, H332	0.1-1%
10294-40-3	barium chromate  Carc. 1A, H350  Acute Tox. 4, H302; Acute Tox. 4, H332	0.1-1%
69012-64-2	Silica-amorphous silica fume	0.1-1%

**Additional information:** For the wording of the listed Hazard Statements, refer to section 16.

#### Notable Trace Components (< 0.1% w/w)

7758-97-6	lead chromate	 Carc. 1B, H350; Repr. 1A, H360; STOT RE 2, H373
-----------	---------------	---

## 4 First-aid measures

(Cont'd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 01, 2019

Revision: February 01, 2019

**Trade name: Stinger® 32-Caliber Rubber Balls**  
**Stinger® 32-Caliber Rubber Balls w/Safety Clip**

(Cont'd. of page 2)

- **Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**  
 Unlikely route of exposure.  
 Brush off loose particles from skin.  
 If skin irritation is experienced, consult a doctor.
- **After eye contact:**  
 Remove contact lenses if worn.  
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Most important symptoms and effects, both acute and delayed:** Blast injury if mishandled.
- **Danger:** Danger of blast or crush-type injuries.
- **Indication of any immediate medical attention and special treatment needed:**  
 Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
 Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.
- **For safety reasons unsuitable extinguishing agents:** None.
- **Special hazards arising from the substance or mixture**  
 Fire or projection hazard.  
 During heating or in case of fire poisonous gases are produced.  
 Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.
- **Advice for firefighters**
- **Protective equipment:**  
 Wear self-contained respiratory protective device.  
 Wear fully protective suit.
- **Additional information:**  
 Eliminate all ignition sources if safe to do so.  
 Cool endangered receptacles with water spray.  
 In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.  
 Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions.  
 Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
 FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material  
 (Cont'd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 01, 2019

Revision: February 01, 2019

**Trade name: Stinger® 32-Caliber Rubber Balls**  
**Stinger® 32-Caliber Rubber Balls w/Safety Clip**

(Cont'd. of page 3)

should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.

Wear protective equipment. Keep unprotected persons away.

Remove persons from danger area.

Ensure adequate ventilation.

Protect from heat.

Isolate area and prevent access.

· **Environmental precautions** No special measures required.

· **Methods and material for containment and cleaning up**

Pick up mechanically.

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

· **Handling**

· **Precautions for safe handling:** Handle with care. Avoid jolting, friction and impact.

· **Information about protection against explosions and fires:**

Protect from heat.

Emergency cooling must be available in case of nearby fire.

· **Conditions for safe storage, including any incompatibilities**

· **Requirements to be met by storerooms and receptacles:**

Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from flammable substances.

· **Specific end use(s)** No relevant information available.

## 8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

### 7429-90-5 Aluminium

PEL (USA) Long-term value: 15\*; 5\*\* mg/m<sup>3</sup>

\*Total dust; \*\* Respirable fraction

REL (USA) Long-term value: 10\* 5\*\* mg/m<sup>3</sup>

as Al\*Total dust\*\*Respirable/pyro powd./welding f.

TLV (USA) Long-term value: 1\* mg/m<sup>3</sup>

as Al; \*as respirable fraction

EL (Canada) Long-term value: 1.0 mg/m<sup>3</sup>

(Cont'd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 01, 2019

Revision: February 01, 2019

**Trade name: Stinger® 32-Caliber Rubber Balls**  
**Stinger® 32-Caliber Rubber Balls w/Safety Clip**

(Cont'd. of page 4)

EV (Canada)	respirable, as Al Long-term value: 5 mg/m <sup>3</sup> aluminium-containing (as aluminium)
LMPE (Mexico)	Long-term value: 1* mg/m <sup>3</sup> A4, *fracción respirable

### 7440-50-8 Copper

PEL (USA)	Long-term value: 1* 0.1** mg/m <sup>3</sup> as Cu *dusts and mists **fume
REL (USA)	Long-term value: 1* 0.1** mg/m <sup>3</sup> as Cu *dusts and mists **fume
TLV (USA)	Long-term value: 1* 0.2** mg/m <sup>3</sup> *dusts and mists; **fume; as Cu
EL (Canada)	Long-term value: 1* 0.2** mg/m <sup>3</sup> *dusts and mists; **fume, as Cu
EV (Canada)	Long-term value: 0.2* 1** mg/m <sup>3</sup> as copper, *fume; **dust and mists
LMPE (Mexico)	Long-term value: 0.2* 1** mg/m <sup>3</sup> *humo (como Cu); **polvo y niebla (como Cu)

### 9004-34-6 cellulose

PEL (USA)	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV (USA)	Long-term value: 10 mg/m <sup>3</sup>
EL (Canada)	Long-term value: 10* 3** mg/m <sup>3</sup> *total dust, **respirable fraction
EV (Canada)	Long-term value: 10 mg/m <sup>3</sup> paper fibre, total dust
LMPE (Mexico)	Long-term value: 10 mg/m <sup>3</sup>

### 592-87-0 lead dithiocyanate

PEL (USA)	Long-term value: 5 mg/m <sup>3</sup> as CN; Skin
EV (Canada)	Long-term value: 0.05 mg/m <sup>3</sup> as Pb, Skin (organic compounds)

### 10294-40-3 barium chromate

PEL (USA)	Long-term value: 0.005* mg/m <sup>3</sup> Ceiling limit value: 0.1** mg/m <sup>3</sup> *as Cr(VI) **as CrO <sub>3</sub> ; see 29 CFR 1910.1026
REL (USA)	Long-term value: 0.0002 mg/m <sup>3</sup> as Cr; See Pocket Guide Apps. A and C
TLV (USA)	Short-term value: 0.0005 mg/m <sup>3</sup> Long-term value: 0.0002 mg/m <sup>3</sup> as Cr; inhalable, DSEN, RSEN

(Cont'd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 01, 2019

Revision: February 01, 2019

**Trade name: Stinger® 32-Caliber Rubber Balls**  
**Stinger® 32-Caliber Rubber Balls w/Safety Clip**

(Cont'd. of page 5)

EL (Canada)	Long-term value: 0.01 mg/m <sup>3</sup> as Cr; ACGIH A1, IARC 1; S(D), S(R)
LMPE (Mexico)	Long-term value: 0.01 mg/m <sup>3</sup> A1; como Cr

### 69012-64-2 Silica-amorphous silica fume

TLV (USA)	TLV withdrawn
EL (Canada)	Long-term value: 4* 1.5** mg/m <sup>3</sup> fume *total; **respirable
EV (Canada)	Long-term value: 2 mg/m <sup>3</sup> respirable
LMPE (Mexico)	Long-term value: 2 mg/m <sup>3</sup> (j)

### · Ingredients with biological limit values:

#### 10294-40-3 barium chromate

BEI (USA)	25 µg/L Medium: urine Time: end of shift at end of workweek Parameter: Total chromium (fume)
	10 µg/L Medium: urine Time: increase during shift Parameter: Total chromium (fume)

### · Exposure controls

#### · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.  
 Keep away from foodstuffs, beverages and feed.  
 Wash hands before breaks and at the end of work.

· **Engineering controls:** Provide adequate ventilation.

· **Breathing equipment:** Not required under normal conditions of use.

#### · Protection of hands:

Wear gloves for the protection against mechanical hazards according to OSHA and NIOSH rules.

#### · Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· **Body protection:** Protective work clothing

#### · Limitation and supervision of exposure into the environment

No relevant information available.

#### · Risk management measures

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

No relevant information available.

(Cont'd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 01, 2019

Revision: February 01, 2019

**Trade name: Stinger® 32-Caliber Rubber Balls**  
**Stinger® 32-Caliber Rubber Balls w/Safety Clip**

(Cont'd. of page 6)

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · Appearance:

**Form:** Solid metal container containing liquid and solid contents.  
**Color:** According to product specification

· **Odor:** Odorless

· **Odor threshold:** Not determined.

· **pH-value:** Not applicable.

· **Melting point/Melting range:** Not determined.

· **Boiling point/Boiling range:** Not determined.

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not determined.

· **Auto-ignition temperature:** Not determined.

· **Decomposition temperature:** Not determined.

· **Danger of explosion:** Heating may cause an explosion.

#### · Explosion limits

**Lower:** Not determined.

**Upper:** Not determined.

· **Oxidizing properties:** Contains oxidizing agent.

· **Vapor pressure:** Not applicable.

· **Density:** Not determined.

· **Relative density:** Not determined.

· **Vapor density:** Not applicable.

· **Evaporation rate:** Not applicable.

#### · Solubility in / Miscibility with

**Water:** Insoluble.

· **Partition coefficient (n-octanol/water):** Not determined.

#### · Viscosity

**Dynamic:** Not applicable.

**Kinematic:** Not applicable.

· **Other information** No relevant information available.

## 10 Stability and reactivity

· **Reactivity:** No relevant information available.

· **Chemical stability:**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used and stored according to specifications.

· **Possibility of hazardous reactions**

Danger of explosion.

(Cont'd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 01, 2019

Revision: February 01, 2019

**Trade name: Stinger® 32-Caliber Rubber Balls**  
**Stinger® 32-Caliber Rubber Balls w/Safety Clip**

(Cont'd. of page 7)

- Toxic fumes may be released if heated above the decomposition point.
- Reacts with strong acids and alkali.
- Reacts violently with oxidizing agents.
- **Conditions to avoid** Sources of ignition, open flame, incompatible materials.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**
  - Carbon monoxide and carbon dioxide
  - Nitrogen oxides
  - Sulfur oxides (SOx)

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:**
  - Based on available data, the classification criteria are not met.
  - Not a skin irritant in unused form. Vapors/particles from used product are possibly irritating to skin.
- **On the eye:**
  - Based on available data, the classification criteria are not met.
  - Not an eye irritant in unused form. Vapours/particles from used product are possibly irritating to eyes.
- **Sensitization:** Based on available data, the classification criteria are not met.

- **IARC (International Agency for Research on Cancer):**

592-87-0	lead dithiocyanate	2B
10294-40-3	barium chromate	1

- **NTP (National Toxicology Program):**

592-87-0	lead dithiocyanate	R
10294-40-3	barium chromate	K

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

- **Probable route(s) of exposure:**
  - Ingestion.
  - Inhalation.
  - Eye contact.
  - Skin contact.
- **Acute effects (acute toxicity, irritation and corrosivity):** Danger of blast or crush-type injuries.
- **Repeated dose toxicity:** No relevant information available.
- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

(Cont'd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 01, 2019

Revision: February 01, 2019

**Trade name: Stinger® 32-Caliber Rubber Balls**  
**Stinger® 32-Caliber Rubber Balls w/Safety Clip**

(Cont'd. of page 8)

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** May be accumulated in organism
- **Mobility in soil:** No relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information**
- **General notes:**  
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
 The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary.  
 Harmful to aquatic organisms  
 Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.  
 After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.  
 The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |                                       |                          |
|---------------------------------------|--------------------------|
| · <b>UN-Number</b>                    |                          |
| · <b>DOT, ADR/RID/ADN, IMDG, IATA</b> | UN0452                   |
| · <b>UN proper shipping name</b>      |                          |
| · <b>DOT, IMDG, IATA</b>              | GRENADES, PRACTICE       |
| · <b>ADR/RID/ADN</b>                  | 0452, GRENADES, PRACTICE |

(Cont'd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 01, 2019

Revision: February 01, 2019

**Trade name: Stinger® 32-Caliber Rubber Balls**  
**Stinger® 32-Caliber Rubber Balls w/Safety Clip**

(Cont'd. of page 9)

· **Transport hazard class(es)**

· **DOT**



· **Class** 1.4  
 · **Label** 1.4G

· **ADR/RID/ADN, IMDG, IATA**



· **Class** 1.4  
 · **Label** 1.4G

· **Packing group**

· **DOT, ADR/RID/ADN, IMDG, IATA** II

· **Environmental hazards**

Not applicable.

· **Special precautions for user**

Not applicable.

· **EMS Number:**

F-A,S-Q

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On cargo aircraft only: 75 kg

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **United States (USA)**

· **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

7429-90-5 Aluminium

7757-79-1 Potassium nitrate

7440-50-8 Copper

(Cont'd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 01, 2019

Revision: February 01, 2019

**Trade name: Stinger® 32-Caliber Rubber Balls**  
**Stinger® 32-Caliber Rubber Balls w/Safety Clip**

(Cont'd. of page 10)

7440-66-6 | zinc metal

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

592-87-0 | lead dithiocyanate

10294-40-3 | barium chromate

7758-97-6 | lead chromate

· **Chemicals known to cause developmental toxicity for females:**

10294-40-3 | barium chromate

7758-97-6 | lead chromate

· **Chemicals known to cause developmental toxicity for males:**

10294-40-3 | barium chromate

7758-97-6 | lead chromate

· **Chemicals known to cause developmental toxicity:**

10294-40-3 | barium chromate

7758-97-6 | lead chromate

· **EPA (Environmental Protection Agency):**

7778-74-7 | Potassium perchlorate

NL

7440-50-8 | Copper

D

7440-66-6 | zinc metal

D, I, II

10294-40-3 | barium chromate

A(inh), D(oral), K/L(inh), CBD(oral)

· **IARC (International Agency for Research on Cancer):**

10294-40-3 | barium chromate

1

69012-64-2 | Silica-amorphous silica fume

3

· **Canadian Domestic Substances List (DSL) (Substances not listed.):**

All ingredients listed on DSL or NDSL.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

(Cont'd. on page 12)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: February 01, 2019

Revision: February 01, 2019

**Trade name: Stinger® 32-Caliber Rubber Balls**  
**Stinger® 32-Caliber Rubber Balls w/Safety Clip**

(Cont'd. of page 11)

OSHA: Occupational Safety &amp; Health Administration

Expl. 1.4: Explosives – Division 1.4

Pyr. Sol. 1: Pyrophoric solids – Category 1

Water-react. 1: Substances and mixtures which in contact with water emit flammable gases – Category 1

Water-react. 2: Substances and mixtures which in contact with water emit flammable gases – Category 2

Ox. Sol. 1: Oxidizing solids – Category 1

Ox. Sol. 2: Oxidizing solids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Carc. 1A: Carcinogenicity – Category 1A

Carc. 2: Carcinogenicity – Category 2

Repr. 1A: Reproductive toxicity – Category 1A

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

**Sources**

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)